

Europäisches Patentamt  
European Patent Office  
Office européen des brevets



(11) EP 1 250 896 A1

(12) EUROPEAN PATENT APPLICATION

(43) Date of publication:  
23.10.2002 Bulletin 2002/43

(51) Int Cl.7: A61C 19/00

(21) Application number: 02007527.1

(22) Date of filing: 02.04.2002

(84) Designated Contracting States:  
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU  
MC NL PT SE TR  
Designated Extension States:  
AL LT LV MK RO SI

(30) Priority: 30.03.2001 JP 2001101967

(71) Applicants:  
• National Institute of Advanced Industrial  
Science and Technology  
Tokyo 100-8921 (JP)  
• USHIO DENKI KABUSHIKI KAISYA  
Tokyo-to, 100-0004 (JP)  
• EVIS Inc.  
Shimoagata-gun, Nagasaki 817-0001 (JP)  
• Nonami, Toru  
Nagoya-shi, Aichi, 463-8560 (JP)

(72) Inventors:  
• Eguchi, Hiromasa  
Himeji-shi, Hyogo 671-1102 (JP)  
• Takami, Kazutomo  
Yokohama-shi, Kanagawa 240-0025 (JP)  
• Ishibashi, Takuro  
Shimoagata-gun, Nagasaki 817-0001 (JP)  
• Nonami, Toru, Aist Chubu,  
Nat.Inst.of Adv. Indust.  
Moriyama-ku, Nagoya-shi, Aichi 463-8560 (JP)

(74) Representative:  
Ebner von Eschenbach, Jennifer et al  
Ladas & Parry,  
Dachauerstrasse 37  
80335 München (DE)

(54) Discolored teeth bleaching system

(57) A system for bleaching discolored teeth is provided. This system has a function of irradiating light emitted from a light-emitting section (9) to the surface of teeth to which a chemical agent including titanium dioxide and hydrogen peroxide has been applied, the irradiation energy of wavelength 380 to 420nm of the light emitted from the light-emitting section is at least 37mW/cm<sup>2</sup> and the ratio of irradiation energy of wavelength 380 to 420nm with respect to the irradiation energy of wavelength 200 to 800nm is at least 36% at this light-emitting section (9), and whereby it is possible to obtain high bleaching effect of the teeth, to reduce the heat applied to the teeth to a low level (no more than 40°C) and to reduce emission of ultraviolet light that has an adverse effect on the human body to a low level.




Fig. 5

## Description

BACKGROUND OF THE INVENTION1. Field of the Invention

[0001] The present invention relates to a system for bleaching discolored teeth, used for bleaching pigments (coloration, discoloration) deposited on teeth, and more particularly, it relates to a system for bleaching discolored teeth, having a function of irradiating with light for bleaching teeth by a photocatalytic action, wherein a chemical agent comprising titanium dioxide and aqueous hydrogen peroxide is applied to the surface of the teeth and these are irradiated with the light.

2. Description of the Related Art

[0002] In recent years, in dental therapy, demands for so-called cosmetic improvements, in which the contour, alignment and integrity etc of the teeth are improved are increasing. Of these, recently, cases in which young women are seeking dental therapy with a view to whitening the teeth, as an important element in facial beauty, are increasing. Causes of dental discoloration or pigmentation/staining may be generally divided into so-called extrinsic causes such as for example deposition of colored substances (tobacco, tea stains and the like), pigment-generating bacteria, discoloration of repair materials (chiefly composite resin), or metallic salts (chiefly amalgam, silver nitrate, or ammonia silver) and so-called intrinsic causes such as for example aging, chemical substances or chemical agents (fluorine, tetracycline and the like), dysmetabolism or hereditary diseases, or dental injuries; however, in dental health therapy, the chief applications of the bleaching method are in the latter i.e. intrinsic cases, where there is dental discoloration of pulpless teeth.

[0003] Several methods have been proposed in the past as methods for the cosmetic improvement of discolored teeth, among which bleaching may be considered a highly effective method for the preservation of dentine, despite drawbacks such as occasional recurrence, when methods suited to individual cases are selected and properly carried out.

[0004] Bleaching is essentially a method for decolorizing colored substances by means of a chemical reaction. In the past there have been various reports of bleaching agents comprising a variety of chemical agents based on vital bleaches and non-vital bleaches, as well as bleaching methods involving the use of such agents.

[0005] The following are some typical examples.

1) Methods of bleaching using 30%  $H_2O_2$  as the chemical agent, with combined use of light and heat on the aqueous hydrogen peroxide.

2) Bleaching using 30%  $H_2O_2$  as the chemical agent, and the concurrent use of high frequency current on the aqueous hydrogen peroxide.

3) Bleaching in which a paste comprising Aerosil (silica fine powder) mixed with 35%  $H_2O_2$  is used as the chemical agent, and the aqueous hydrogen peroxide and Aerosil paste is applied.

4) Bleaching in which a paste obtained by kneading a 35%  $H_2O_2$  solution and a powder (ingredients comprising potassium sulfate, manganese sulfate, silicon dioxide, or the like) is used as the chemical agent (MATSUKAZE HIGHLIGHT, Trademark).

5) Bleaching in which a mixture of 1 mL of 30% HCl, 1 mL of 30%  $H_2O_2$ , and 0.2 mL of diethyl ether is used as the chemical agent (improved MacInnes bleaching).

6) A method in which a kneaded paste of 30%  $H_2O_2$  and a sodium perborate powder is used as the chemical agent (working bleach method).

[0006] Many other bleaching methods have also been reported, such as the dental bleaching agent and method comprising a mixture of aqueous hydrogen peroxide and ortho-phosphoric acid (Japanese Laid-Open Patent Publication No. H8-143436/1996), the bleaching agent comprising a mixture of silicic anhydride with aqueous hydrogen peroxide, and the vital bleaching method comprising the application of such a bleaching agent (Japanese Laid-Open Patent Publication No. H5-320033/1993), and the dental bleaching composition comprising a dental bleaching agent (such as hydrogen-urea peroxide, hydrogen peroxide-carbamide, and carbamide peroxide) and a matrix material (such as carboxymethylene), a method for bleaching teeth using the above (Japanese Laid-Open Patent Publication No. H8-113520/1996) and a method for bleaching discolored teeth using photocatalysis of titanium dioxide (published Japanese Patent No. 3030380/2000).

[0007] As can be seen from the foregoing prior art, a technique is known to perform bleaching of pigment deposited on teeth (coloration, discoloration) by combining irradiation with light with a chemical agent based on titanium dioxide

and aqueous hydrogen peroxide. For example, in the above Japanese Patent publication No. 3030380, regarding the irradiation with light, it is merely stated that, although it is desirable to perform the irradiation with high-energy ultraviolet light, from the point of view of generating activated oxygen by the photocatalytic effect and from the point of view of its oxidative action, since ultraviolet light affects the human body, it is desirable to perform irradiation with violet light. However, what kind of light is actually effective is not known, and the details thereof are not known.

[0008] Also, the bleaching function changes considerably depending on the concentration of the aqueous hydrogen peroxide. When aqueous hydrogen peroxide is introduced into the mouth, in the case of aqueous hydrogen peroxide of high concentration, there is an adverse effect on the human body and in recent years, in accordance with various tests, from the point of view of both bleaching and safety, the concentration of aqueous hydrogen peroxide is determined as 3%.

[0009] However, the optimum conditions for light and chemical agents including 3% aqueous hydrogen peroxide have not been discovered; for example, even if a specific type of light has a bleaching function, heat is also generated by irradiation with light, so that the tooth crown is heated whilst bleaching, causing inflammation of the pulp; or there was the problem of emission of ultraviolet light, which has an adverse effect on the human body.

#### SUMMARY OF THE INVENTION

[0010] The present invention has been made in view of the above, its object is to provide a system for bleaching discolored teeth, wherein, when bleaching teeth using a chemical agent comprising titanium dioxide and aqueous hydrogen peroxide, reliable bleaching of the teeth can be achieved, yet little heat is applied to the teeth and essentially no ultraviolet light that has an adverse effect on the human body is irradiated.

[0011] The present invention, in order to solve the above problem, comprises the following technical means:

[0012] A system for bleaching discolored teeth, which has a function of irradiating light emitted from a light-emitting section to the surface of the teeth to which a chemical agent comprising titanium dioxide and hydrogen peroxide has been applied, wherein the irradiation energy of wavelength 380 to 420 nm of the light emitted from the light-emitting section is at least 37 mW/cm<sup>2</sup>, and the ratio of irradiation energy of wavelength 380 to 420 nm with respect to the irradiation energy of wavelength 200 to 800 nm is at least 36% at the light-emitting section.

[0013] The system for bleaching discolored teeth according to the above, wherein said system has a light-guide member, the tip of which light-guide member is the light-emitting section.

#### BRIEF DESCRIPTION OF THE DRAWINGS

[0014]

Figure 1 is a diagram of a system for bleaching discolored teeth according to an embodiment of the present invention;

Figure 2 is a diagram of a metal halide lamp employed as light source in the embodiment;

Figure 3 is a diagram of a halogen incandescent lamp employed as light source in the embodiment;

Figure 4 is a spectral distribution diagram of the light source (metal halide lamp) unit of system 5;

Figure 5 is a spectral distribution diagram of the light emitted from the light-emitting section of system 5;

Figure 6 is a spectral distribution diagram of the light emitted from the light-emitting section of system 6;

Figure 7 is a spectral distribution diagram of the light emitted from the light-emitting section of system 8;

Figure 8 is a spectral distribution diagram of a light source (halogen incandescent lamp) of system 10; and

Figure 9 is a spectral distribution diagram of the light emitted from the light-emitting section of system 10.

#### DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0015] Next, the present invention is further described in detail.

[0016] As described above, in the system according to the present invention, the light emitted from the light-emitting section satisfies the following conditions:

irradiation energy of 380 to 420 nm thereof is at least 37 mW/cm<sup>2</sup> and the ratio of irradiation energy of 380 to 420 nm with respect to the irradiation energy of 200 to 800 nm is at least 36%. Other constructions in the system, for example, means such as the light source, filter or light-guide member, may be preferably selected and is not subject to any particular restriction.

[0017] The system for bleaching discolored teeth of the present invention has the function of directing light emitted from the light source to light-emitting section by the light-guide member, and irradiating the light onto the surface of

teeth to which a chemical agent comprising titanium dioxide and aqueous hydrogen peroxide has been applied; it has the capability of completing bleaching of the teeth in about five minutes.

[0018] The ability to complete bleaching in five minutes is a very important factor in implementing an optical irradiation system, since, normally, it is difficult for a patient receiving treatment to maintain the mouth in an open condition for more than five minutes.

[0019] Figure 1 shows an example of the construction of a system for bleaching discolored teeth according to the present invention.

[0020] In Figure 1, 1 is a light device, 2 is a light source (lamp), 3 is a mirror, 4 is a power source, 5 is a cooling fan, 6 is a wavelength cut-off filter, 7 is a light-guide member, 8 is a light-guide, 9 is a light-emitting section and 10 is a holder. 1a indicates a light-emitting section of the light device that emits light passing through a wavelength cut-off filter formed on the light device 1.

[0021] In the system as described above, preferably a meta-hala (metal halide lamp) or halogen (halogen incandescent lamp) is employed as the light source (lamp). As the wavelength cut-off filter, a single or a plurality of filters may be employed, for example, an infra-red cut-off filter that cuts off wavelengths of 800 nm or more, a cold filter that passes wavelengths of the region 200 to 450 nm, a blue filter that passes wavelengths centered on 400 nm or a wavelength selection filter that passes wavelengths of the region 380 to 420 nm but does not pass other wavelengths or the like. Also, as a light-guide member, preferably an optical fiber may be employed.

[0022] The light emitted from light source 2 is collected by mirror 3 and adjusted to light of a specified wavelength region by a single or a variety of wavelength cut-off filters 6, and is directed to light-emitting section 9 through light-guide member 7 and light-guide 8, and is irradiated onto the surface of the teeth through this light-emitting section 9.

[0023] The light emitted from light-emitting section 9 in the system described above must satisfy the following conditions.

[0024] The light emitted from light-emitting section 9 must have a condition 1 that a irradiation energy of wavelength 380 to 420 nm of the light is at least 37 mW/cm<sup>2</sup>.

[0025] This condition is determined taking into account the fact that a chemical agent comprising titanium dioxide and aqueous hydrogen peroxide has an excellent bleaching effect in the wavelength region of 380 to 420 nm, the fact that, when the emitted energy is less than 37 mW/cm<sup>2</sup>, the energy is small so that a very long time is taken to achieve bleaching, which means that the patient undergoing treatment must keep his mouth open for at least 5 minutes, and that, when the emitted energy is at least 37 mW, a reliable bleaching effect can be expected within 5 minutes.

[0026] The light emitted from light-emitting section 9 must have a condition 2 that the ratio of the irradiation energy at 380 to 420 nm with respect to the irradiation energy of wavelength 200 to 800 nm is at least 36%.

[0027] This condition is determined with a view to reducing the amount of light on the long wavelength side, which constitutes heat energy, and to achieving efficient irradiation with light in the wavelength region 380 to 420 nm, which contributes to the bleaching effect.

[0028] Preferably the ratio of irradiation energy of 380 nm or less is no more than 5% with respect to the irradiation energy of wavelength 200 to 800 nm.

[0029] This is in order to reduce the amount of ultraviolet radiation, which has an adverse effect on the human body. It is believed that there are no adverse effects on the human body so long as the ratio of irradiation energy of no more than 380 nm is no more than 5%.

[0030] Although condition 1 and condition 2 described above were explained with reference to light emitted from light-emitting section 9, if no light guide member 7 is required, a light device of the light-emitting section 1a of the light device 1 has the same role and function as light-emitting section 9 described above. In this case, the light emitted from the light device of the light-emitting section 1a is directly incident on the surface of the teeth, so it must satisfy condition 1 and condition 2 above.

[0031] That is, as shown in Figure 1, with regard to the light-emitting section in the invention of the present application, if a light-guide member 7 is provided, the light emitting section is light-emitting section 9, but if light-guide member 7 is not required, the light emitting section is light device of the light-emitting section 1a.

[0032] In the present invention, a chemical agent comprising titanium dioxide and hydrogen peroxide is employed, but, as a preferable aspect thereof, there may be mentioned by way of example a chemical agent consisting of a solution/paste of titanium dioxide powder and aqueous hydrogen peroxide of low concentration (preferably, no more than 6%). In this case, as the titanium dioxide, for example, titanium dioxide of particle size about 5 to 60 nm, in particular, titanium dioxide fine particles of the anatase type or material consisting chiefly thereof may be preferably employed, but there is no restriction to these and any material having the same effects as these may be employed in the same way irrespective of its form or shape. Material of small particle size is particularly preferred since it has the advantages that high photocatalytic activity can be expected, the amount to be deposited on the teeth need only be small, the amount to be used can be reduced, and, since the applied film is thin, for example, a high bleaching effect is obtained in a short time (within five minutes).

[0033] The ratios of the amounts of the above constituents can be preferably altered and adjusted for example for

the cases of light discoloration and severe discoloration and in this way a range of products can be prepared preferable for various cases.

[0034] The chemical agent used in the present invention is employed in the form of a uniform transparent solution or paste by blending, kneading and dispersing fine titanium dioxide powder in low-concentration aqueous hydrogen peroxide, but there is no restriction to these and preparations obtained in the same way as these could be likewise employed. There is no particular restriction regarding the preparation means or device and the like for the chemical agent and preferable means or devices may be employed. In the present invention, application of the chemical agent to the surface of the teeth means coating and depositing this chemical agent onto the surface of the teeth, there being no particular restriction regarding the coating means. Furthermore, although, in the present invention, normally, the above chemical agent is employed in a form in which the above two constituents are used together as active constituents, it would be possible for these constituents to be prepared separately and combined when used.

[0035] In the present invention, light emitted from the light-emitting section of a system according to the present invention is directed onto the surface of teeth to which the aforesaid chemical agent is applied, wherein application of the chemical agent to the surface of the teeth and irradiation with light to the teeth could be performed once or repeated a few times. The extent and the number of times of application of this chemical agent and irradiation with light can be preferably adjusted in accordance with the degree of severity of the discoloration of the teeth.

[0036] The chief function of the chemical agent comprising titanium dioxide and hydrogen peroxide employed in the present invention and irradiation with light using the system of the present invention is a bleaching function produced by the synergetic effect of photocatalytic activation of the titanium dioxide by irradiation with light and the bleaching function produced by the aqueous hydrogen peroxide of low concentration (preferably, no more than 6%). When titanium dioxide having photocatalytic activity is irradiated with light, electrons and positive holes are generated, which react with the hydrogen peroxide to produce active oxygen. This active oxygen has a much more powerful oxidizing effect than ozone and is capable of oxidative decomposition of practically all organic substances to carbon dioxide. Even n-type semiconductor titanium oxide, which has a comparatively large band gap, for example, in the case where it is employed as a solution with aqueous hydrogen peroxide, easily generates active oxygen having a powerful oxidative effect on irradiation with light, as a result of which the values of charge dissociation, electron/hole mobility, and proton/hydroxyl group reaction are substantially raised compared with when this is employed on its own, producing a synergetic bleaching effect when combined with the oxidative action of the aqueous hydrogen peroxide itself. Thus, essentially, the photocatalytic function that can only be produced by irradiation with ultraviolet light of wavelength no more than 380 nm having energy corresponding to the band gap of titanium dioxide can be produced by irradiation with light produced by the system according to the present invention.

[0037] Next, in order to give a specific description of a system according to the present invention, systems incorporating various types of lamps were manufactured and tests were conducted. The test items and the results are shown in Table 1.

#### (1) Systems

[0038] Systems 1 to 11 incorporating various types of lamp and filter were employed for the system shown in Figure 1.

#### (2) Test method

[0039] Tests of bleaching of discolored teeth by application of the chemical agent and irradiation with light using systems 1 to 11 were conducted.

[0040] As the chemical agent, there was employed a solution obtained by mixing 0.5 g of titanium dioxide powder with 1 ml of 3%  $H_2O_2$ ; this chemical agent was applied to the discolored teeth and the surfaces of the teeth, 1 mm in front of the end of the light-emitting section, were irradiated with light from emitting sections of systems 1 to 11.

#### (3) Light source

[0041] In these tests, meta-halals (metal halide lamps) and halogens (halogen incandescent lamps) were employed as the light source. The details of the specifications of these are described below.

##### 1) Metal halide lamps

[0042] Figure 2 is a diagram of a metal halide lamp: a light-emitting tube 10 made of quartz glass has an approximately spherical shape, with an maximum internal diameter of 9 mm $\phi$  and an internal volume of 0.4 cc. Molybdenum foils 31 and 32 are respectively embedded in a sealed section 11 on the cathode side and a sealed section 12 on the anode side at both ends of light-emitting tube 10, cathode 21 and anode 22 base sections respectively connected to molyb-

denum foils 31 and 32 being arranged facing each other within light-emitting tube 10. An external inlet rod 41 on the cathode side with one end thereof welded to molybdenum foil 31 extends from the sealed section 11 on the cathode side and an external inlet rod 42 on the anode side with one end thereof welded to molybdenum foil 32 extends from the sealed section 12 on the anode side.

**[0043]** Mercury and argon constituting a rare gas for start-up are sealed within light-emitting tube 10. A halide of a light-emitting metal is sealed therein as the light-emitting metal, in order to improve color rendering and the like, indium, dysprosium, holmium, erbium, thulium, cerium, praseodymium, neodymium, lutetium, gadolinium or cesium etc may be employed; as the halogen, iodine or bromine may be employed.

**[0044]** In the present tests, a device ignited with a rating of 70 V, 1.9 A having sealed therein 15.0 mg of mercury, 20 kPa of argon, 0.5 mg of dysprosium iodide and cesium iodide composite, 0.3 mg of mercury iodide and 0.1 mg of indium iodide was employed

## 2) Halogen incandescent lamp

**[0045]** Figure 3 illustrates a halogen incandescent lamp. This has a sealed section 12 at one end formed with a gas-tight sealed section produced by pinch sealing and at its other end has an exhaust tube residual section 13, comprising, for example, a bulb 11 made of hard glass with a tungsten filament coil 14 arranged extending in a direction orthogonal to the tube axis of this bulb 11 within this bulb 11.

**[0046]** For example, inert gas and a halogen compound are sealed within bulb 11.

**[0047]** One internal lead rod 15a is connected with one end of filament coil 14 while another internal lead rod 15b is connected with the other end thereof. The tips of this one internal lead rod 15a and the other internal leader rod 15b respectively extend into sealed sections 12 and in these sealed sections 12 are connected with a pair of metal foils 16a and 16b which are embedded in mutually separated fashion. One external lead rod 17a and another external lead rod 17b extending to the outside from sealed sections 12 are respectively connected with respective metal foils 16a and 16b.

**[0048]** In these tests, a device ignited with a rating of 12 V, 8.3 A was employed.

Table 1

	Light source	Irradiation energy of 380 to 420 nm (mW/cm <sup>2</sup> )	Bleaching effect (irradiation time: 5 minutes)	% of irradiation energy of 380 to 420 nm/200 to 800 nm	Whether or not the temperature of the tooth pulp exceeds 40 °C (irradiation time: 5 minutes)	Percentage of irradiation energy of 380 nm or less/200 to 800 nm	Total results of evaluation
System 1	Halogen	44.8	*	18	Exceeds	-	X
System 2	Meta-hala	29.6		-	-	-	X
System 3	Meta-hala	50.1	**	17.6	Exceeds	-	X
System 4	Meta-hala	47.8	**	43.9	Not exceed	28.6	X
System 5	Meta-hala	72.9	***	39.3	Not exceed	0.8	O
System 6	Meta-hala	64.7	***	40.7	Not exceed	0.5	O
System 7	Meta-hala	37.5	*	22.5	Exceeds	-	X
System 8	Meta-hala	87.1	***	36.1	Not exceed	0.5	O
System 9	Halogen	46.8	*	27.4	Exceeds	-	X
System 10	Halogen	55.6	***	83.1	Not exceed	3.1	O
System 11	Halogen	64.1	***	16.4	Exceeds	-	X
		37 or more		36 or more		Less than 5	

\*: There exists the bleaching effect, and the degree thereof increases according as the number of asterisk increases.  
 X shows "no good" and O shows "good".

## (4) Test results

[0049] From the above test results, it was found that systems 5, 6, 8 and 10 satisfied all of the above conditions 1 and 2 and constituted the best discolored teeth bleaching devices.

[0050] Specifically, in systems 1 to 11, on examining the emission energy at 380 to 420 nm and the bleaching effect (irradiation time: five minutes), no bleaching effect was found in the case of system 2, which was less than 37 mW/cm<sup>2</sup>.

[0051] Next, as a result of examining the ratio of irradiation energy of 380 to 420 nm with respect to the irradiation energy of 200 to 800 nm and whether or not the temperature of the pulp exceeded 40 (irradiation time: five minutes), it was found that, in the case of systems 4 to 6, 8 and 10, in which the ratio of irradiation energy of 380 to 420 nm, which contributes to the bleaching effect, was at least 36%, the temperature of the pulp did not exceed 40.

[0052] Further, as a result of an overall evaluation taking into account the fact that the ratio of irradiation energy of no more than 380 nm with respect to the irradiation energy of 200 to 800 nm or less is less than 5%, it was found that systems 5, 6, 8 and 10 constituted the best devices for bleaching discolored teeth.

[0053] Next, the details of systems 5, 6, 8 and 10 are described.

## 1) System 5

[0054] Figure 4 is a spectral distribution diagram of a discharge lamp (metal halide lamp) unit incorporated in system 5. In Figure 4, the vertical axis indicates relative intensity.

[0055] Figure 5 is a spectral distribution diagram of the light emitted from the light-emitting section of system 5.

[0056] In this system, the following three filters were employed.

Filter 1: infra-red cut-off filter that cuts off above 800 nm;

Filter 2: cold filter that passes 200 to 450 nm; and

Filter 3: blue filter that passes wavelengths centered on 400 nm.

## 2) System 6

[0057] The spectral distribution diagram of the discharge lamp (metal halide lamp) unit incorporated in system 6 is the same as that of Figure 4.

[0058] Figure 6 shows a spectral distribution diagram of the light emitted from the light-emitting section of system 6.

[0059] In this system, the following three filters were employed.

Filter 1: infra-red cut-off filter that cuts off above 800 nm;

Filter 2: cold filter that passes 200 to 450 nm; and

Filter 3: blue filter that passes wavelengths centered on 400 nm.

## 3) System 8

[0060] The spectral distribution diagram of the discharge lamp (metal halide lamp) unit incorporated in system 8 is the same as that of Figure 4.

[0061] Figure 7 shows a spectral distribution diagram of the light emitted from the light-emitting section of system 8.

[0062] In this system, the following filters were employed.

Filter 1: infra-red cut-off filter that cuts off above 800 nm;

Filter 2: cold filter that passes 200 to 450 nm; and

Filter 3: blue filter that passes wavelengths centered on 400 nm

[0063] In system 5, system 6 and system 8, the light-guide member and the intensity of the light were varied, using the same lamp and same filter combination.

## 4) System 10

[0064] Figure 8 is a spectral distribution diagram of an incandescent lamp (halogen lamp) unit incorporated in device 10.

[0065] Figure 9 is a spectral distribution diagram of the light emitted from the light-emitting section of system 10.

[0066] In this system, the following filter was employed:




wavelength selection filter that passes wavelengths in the region 380 to 420 nm but does not pass wavelengths other than these.

[0067] The following effects are obtained by the present invention.


- (1) A system for bleaching discolored teeth can be provided, whereby an excellent bleaching effect can be obtained by irradiating with light the surface of teeth coated with a chemical agent comprising titanium dioxide and hydrogen peroxide.
- (2) A high bleaching effect with an irradiating time of no more than five minutes can be obtained by irradiation with light using the system of the present invention.
- (3) The temperature of the pulp does not exceed 40 (reference time: five minutes).
- (4) The irradiation energy of no more than 380 nm represents less than 5% of the irradiation energy of 200 to 800 nm, so there is no risk of an adverse effect on the human body.
- (5) It is useful as a system for irradiation with light used for bleaching of discolored teeth using a chemical agent comprising titanium dioxide and low-concentration (no more than 6%) hydrogen peroxide.
- (6) The system of the present invention has the distinct advantages that a high degree of bleaching effect of the teeth can be achieved with little heat being supplied to the teeth (less than 40 °C) and emission of ultraviolet radiation, which has an adverse effect on the human body, can be reduced to a low level.

## Claims


1. A system for bleaching discolored teeth, which has a function of irradiating light emitted from a light-emitting section to the surface of the tooth to which a chemical agent comprising titanium dioxide and hydrogen peroxide has been applied, wherein the irradiation energy of wavelength 380 to 420 nm of the light emitted from the light-emitting section is at least 37 mW/cm<sup>2</sup>, and the ratio of irradiation energy of wavelength 380 to 420 nm with respect to the irradiation energy of wavelength 200 to 800 nm is at least 36% at the light-emitting section.
2. The system for bleaching discolored teeth according to claim 1, wherein said system has a light-guide member, the tip of which light-guide member is the light-emitting section.




F i g . 1




F i g . 2




F i g. 3




F i g . 4



F i g . 5




F i g . 7



F i g . 8





F i g . 9



European Patent  
Office

## EUROPEAN SEARCH REPORT

Application Number  
EP 02 00 7527

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X	WO 01 01943 A (ISHIHARA FUKUSABURO ;KAKUDA MINORU (JP); SOTOAKA RYUJI (JP); ISHIB) 11 January 2001 (2001-01-11) * abstract; table 2 *	1	A61C19/00
A	EP 0 242 585 A (DEMETRON RES CORP) 28 October 1987 (1987-10-28) * column 4, line 23 - column 4, line 26; figure 1 *	1,2	
A	EP 1 031 326 A (DECAUDIN JEAN MICHEL) 30 August 2000 (2000-08-30) * column 3, line 4 - column 3, line 9 * * column 4, line 39 - column 4, line 48 * * column 6, line 45 - column 6, line 54 * * column 7, line 36 - column 7, line 43 *	1,2	
A	EP 1 048 291 A (JAPAN REPRESENTED BY DIRECTOR ;NONAMI TORU (JP); TOADA HIROSHI (JP) 2 November 2000 (2000-11-02) * the whole document *	1	
A	US 4 229 658 A (GONSER DONALD I) 21 October 1980 (1980-10-21) * column 4, line 52 - column 4, line 55; figures *	1,2	
The present search report has been drawn up for all claims			
Place of search <b>MUNICH</b>		Date of completion of the search <b>1 July 2002</b>	Examiner <b>Fouquet, M</b>
<p><b>CATEGORY OF CITED DOCUMENTS</b></p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons &amp; : member of the same patent family, corresponding document</p>			

EP0 FORM 1503 03 R2 (P4/C01)

ANNEX TO THE EUROPEAN SEARCH REPORT  
ON EUROPEAN PATENT APPLICATION NO.

EP 02 00 7527

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on  
The European Patent Office is not responsible for these particulars which are merely given for the purpose of information.

01-07-2002

Patent document cited in search report		Publication date		Patent family member(s)	Publication date
WO 0101943	A	11-01-2001	AU	5572400 A	22-01-2001
			EP	1192933 A1	03-04-2002
			WO	0101943 A1	11-01-2001
EP 0242585	A	28-10-1987	US	4661070 A	28-04-1987
			EP	0242585 A1	28-10-1987
			JP	62270151 A	24-11-1987
EP 1031326	A	30-08-2000	FR	2789294 A1	11-08-2000
			FR	2798582 A1	23-03-2001
			AU	2302600 A	25-08-2000
			EP	1031326 A1	30-08-2000
			WO	0045733 A1	10-08-2000
			JP	2000245747 A	12-09-2000
EP 1048291	A	02-11-2000	JP	3030380 B2	10-04-2000
			JP	11092351 A	06-04-1999
			AU	9095698 A	12-04-1999
			EP	1048291 A1	02-11-2000
			US	6231343 B1	15-05-2001
			CN	1270508 T	18-10-2000
			WO	9915143 A1	01-04-1999
US 4229658	A	21-10-1980	AR	218989 A1	15-07-1980
			BR	7905324 A	20-05-1980
			CA	1100167 A1	28-04-1981
			CH	642196 A5	30-03-1984
			DE	2927260 A1	28-02-1980
			DK	334579 A	19-02-1980
			FR	2433704 A1	14-03-1980
			GB	2028994 A , B	12-03-1980
			IT	1209447 B	30-08-1989
			JP	55028973 A	29-02-1980
			MX	145141 A	06-01-1982
			NL	7904642 A	20-02-1980
			NO	792686 A	19-02-1980
			SE	7906874 A	19-02-1980

EPO FORM P0453

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82